



UBT822

TILT DECK TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components.
5-Year Structural Warranty.
Ask us for details.

Trailer details may differ from image

Loads Faster.

Brandt Work Ready™ tilt deck trailers deliver fast loading and unloading to maximize your output. The Lode N Lok™ auto-latching decks save you valuable time while increasing operator safety.

① Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn until the job gets done:

- A unified-frame design integrates the frame and deck into a single robust structure to minimize weak points and stress concentrations.
- Designed for optimal balancing with agricultural or landscape equipment, allowing for the most stable and secure load platform in the industry.
- Reliable design and long-lasting components reduce total cost of ownership.

② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Lode N Lok™ self-locking deck enables faster loading, saving valuable time.
- Torsion spring suspension system delivers reliable shock-absorption without requiring any maintenance work.

③ Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Power Pin™ ball hitch is specially designed to automatically latch, ensuring that the trailer is properly secured to the towing vehicle, every single time.
- Foolproof locking mechanism automatically secures the deck once the equipment is loaded, maximizing safety.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.

Powerful Value. **Delivered.**

Brandt

TILT DECK TRAILERS SPECIFICATIONS

QUICK REFERENCE CHART	UBT822 Tandem Tilt
RELIABILITY - RATED CAPACITY	
GVWR (lb)	16,000
Rated Payload (lb)	12,400
Tongue Weight (lb)	2000
Suspension	Torsion - Bolt On
Axle Rating (lb)	2 x 7000
Maximum Weight on Fixed Deck (lb)	2000
DURABILITY - STRUCTURE & FINISH	
HSS Mainframe Size (in)	8
Pressure-Treated Spruce/Pine Decking	●
Polyurethane Primer & Paint	●
DIMENSIONS	
Total Length (ft)	27.7
Fixed Deck Length (ft)	6
Tilt Deck Length (ft)	16
Deck Width (in) – inside fender to fender	81.5
Deck Height (in)	25
INCLUDED EQUIPMENT	
Pull Type	Bumper
Single Speed Jackleg Lift Capacity (lb)	10,000
Hydraulic Cushion Cylinder	●
Steel Tread Plate Fenders – bolt on	●
Black Steel Wheels	●
Tire Size	ST235/80R16 LRE
Premium Radial Tires – speed rated to 120 kph	10 ply
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES	
4 x 4" D-Rings	●
Premium Protected Wiring	●
Breakaway Switch – includes LED test lights, battery & charger	●
Integral Footholds	●
Lode N Lok Deck	●
Tier 1 LED Lighting System	●
Forward Self-Adjusting Brakes	●
E-Z Lube Grease Axle Bearings	●
Tool Tray	●

AVAILABLE ACCESSORIES: Coupler Lock, Wheel Locks, and Tie Down Kit

● Included at no extra cost